

Specification of "MAX" ~High-floored bed~

Length	2020m m
Width	970m m
Weight (remove a mat)	about90kg
Power	AC100V~240V 50/60H z
Bottom-part clearance	220m m
Operating angle of back lifting	MAX 71.2°
Operating angle of legs lifting	MAX 34.9°
The maximum height from the floor	750m m
The minimum height from the floor	450m m
Back lifting special system	With function of catch prevention by indirect drive
Gatch operating speed	4° /sec
Gatch emergency stop mechanism	Yes
Operation of gatch emergency stop mechanism	Momentary method
High/low operation speed	7.5mm/sec
High/low emergency stop mechanism	Yes
Operation of high/low emergency stop mechanism	Momentary method
Wheel	Yes
Wheel diameter	100mm
The maximum number of parts after disassembling	5
The maximum width of parts after disassembling	890m m
The maximum length of parts after disassembling	1960m m
Weight of the largest part	about70 k g
Fixation of a side rail	Yes
Fixation of an assistant bar	Yes
Compatible mattress	Slider, a mattress to alleviate abdominal pressure (for the width of 830)
color	Ivory/Brown
Features	Lifting of backs and legs, and raising and lowering a bed needed for nursing care is all operated by a remote controller. It can elevate by a maximum of 900mm, which alleviates burden on a carer's back.
Precautions	Please read the operating manual carefully before using it.